



PROFLEX AL



DESCRIPTION

PROFLEX AL is an expansion joint composed of two L-shaped profiles in stainless steel and an expandable insert in vinyl resin / rubber. The profile is equipped with punched flanges that guarantee its anchorage to the support.

MATERIAL

PROFLEX AL is an expansion joint composed of two L-shaped profiles in natural aluminium and an expandable insert in vinyl resin / rubber. It is available in the heights of 4.5 / 6 / 8 / 10 / 12.5 / 15 and 20 mm with a visible surface of 17 mm. The L-shaped profiles, that protect the tiles edges, are equipped with punched flanges that guarantee the anchorage of the joint to the support; they are joined together with an expandable insert in vinyl resin / rubber available in black and grey colour (on demand in ivory and beige). The expandable part, with a visible surface of 11 mm, is fungus, bacteria and UV resistant. Its section and the mechanical resistance, make **PROFLEX AL** a good solution for the realization of expansion joints also in case of heavy traffic.

AREAS OF USE

PROFLEX AL in natural aluminium is suitable for every kind of environment where good resistance to mechanical and chemical stresses are required.

WARNINGS


Do not use **PROFLEX AL** in natural aluminium in swimming pools and in environments where aggressive substances are used. Clean immediately the surface of the profile from all remains of adhesive or grout after laying.

MAINTENANCE

PROFLEX AL does not require any special maintenance. It is suggested to clean it with normal household cleaning products.

LAYING INSTRUCTIONS

1. Choose "**PROFLEX AL**" according to the tile thickness and desired colour.
2. Cut "**PROFLEX AL**" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Place the joint exactly over the screed joint and press the anchoring flange into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. After laying the joint should be 0,5 mm below the floor covering surface. Remove immediately all the remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



TEXT TEMPLATE FOR TENDERS

Delivery and installation of expansion joint, in the height of 8 / 10 / 12.5 / 15 / 20 mm, with a visible surface of 17 mm. It is composed of two L-shaped profiles in natural aluminium connected between them with an expandable insert in vinyl resin / rubber in black / grey colour. The L-shaped profiles are equipped with punched flanges that guarantee the joint anchorage to the support. The expandable insert in vinyl resin / rubber has a visible surface of 11 mm and high chemical and mechanical resistance. It is fungus, bacteria and UV resistant, like PROFLEX AL of the Progress Profiles company.

PFXAL 08 / 10 / 125 / 15 / 20... : Natural aluminium and vinyl resin / rubber.

Prtofile height : _____ mm
 Profile length : _____ mt
 Material : _____ €/mt
 Application : _____ €/mt
 Total value : _____ €/mt