

**PROCOVER** is a joint-cover profile in anodised aluminium. It is applied at the end of laying two adjoining floors with the same height, having left a 6 - 24 mm gap between the two floors set in a thin bed of adhesive. It protects the outside edges of the floor/covering. It is easy to lay and attractive. The design of the profile with lower vertical arrowhead part allows excellent anchorage with the silicone/adhesive.

# PROCOVER

ANODISED SILVER, GOLD ALUMINIUM



**ANODISED SILVER, GOLD ALUMINIUM**

**thermo packed** - bar length 2,7 LM

(PCRAA 1499 bar length 0,90 LM - pack. 40 Pcs



Article	L x H mm
PCRAA 149 (pack. 40 Pcs)	14 x 9
PCRAO 149 (pack. 40 Pcs)	14 x 9
PCRAA 1499 (pack. 40 Pcs)	14 x 9
PCRAA 209 (pack. 40 Pcs)	20 x 9
PCRAA 269 (pack. 40 Pcs)	26 x 9
PCRAO 269 (pack. 40 Pcs)	26 x 9
PCRAA 409 (pack. 20 Pcs)	40 x 9

PCRAA - AO 149 curvable. (See pag. 178)



**COLOURS**



(for a precise assessment of colours and finishes, see the relative enclosed sheet)


Available in the finishes: AA - AO, PCRAA 149 and PCRAA 269 are available on request (minimum purchase quantity: 540 lm - Price: add a +20% to the price of PCRAA 149 and PCRAA 269)




AT - Anod. titanium aluminium AB - Anod. Bronze aluminium

PCR... 149/1499

PCR... 209



PCR... 269  
PCRAA 409



**EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS**



1. Choose the PROCOVER with the width suitable for the gap between the two floors to be joined, taking into consideration 2/3 mm side lap.
2. Fill the gap with single-pack silicone or with the adhesive used for laying the floor.
3. Bury the profile into the adhesive, making sure that both side laps of the profile rest on the coverings to be joined.

**PROCOVER WOOD** is a joint-cover profile in aluminium covered with a very strong film available in 10 wood finishes. It is applied at the end of laying two adjoining floors with the same height, having left a 6 - 24 mm gap between the two floors set in a thin bed of adhesive. It protects the outside edges of the floor/covering. It is easy to lay and attractive. The design of the profile with lower vertical arrowhead part allows excellent anchorage with the silicone/adhesive.

# PROCOVER WOOD

ALUMINIUM COVERED WITH PROTECTIVE FILM IN 10 WOOD FINISHES

**ALUMINIUM 10 WOOD FINISHES thermo packed**

bar length 2,7 LM - pack. 40 Pcs - 108 LM (L 26mm - 54 LM)

Article	L x H mm
PCRA... 149	14 x 9
PCRA... 269	26 x 9

Available in the wood finishes: 05W - 11W - 28W - 29W - 30W (04W, 07W, 08W, 09W, and 10W available upon request with a minimum quantity order of 540 lm). The code of the selected colour must be added to the article code. E.g.: PCRA... 149 (chosen finish light oak) PCRA05W 149.




**COLOURS**

(for a precise assessment of colours and finishes, see the relative enclosed sheet)




UPON REQUEST - MINIMUM QUANTITY 540 LM

PCRA... 149



PCRA... 269



**EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS**



1. Choose the PROCOVER with the width suitable for the gap between the two floors to be joined, taking into consideration 2/3 mm side lap.
2. Fill the gap with single-pack silicone or with the adhesive used for laying the floor.
3. Bury the profile into the adhesive, making sure that both side laps of the profile rest on the coverings to be joined.

# PROCOVER INSERT for inserting Procover profiles

VINYL RESIN / BLACK RUBBER

Vinyl resin/rubber profile "U-form" for inserting PROCOVER with PINBFT 45 or PINBFT 40 Proinsert System base.

**VINYL RESIN/RUBBER**

length 2,7 LM and/or in rolls 100 LM

Article
PCPCR 2,7ML
PCPCR 100ML

**PROINSERT BASE 45 and BASE 40 - ALU. PUNCHED - PERFORED** - bar length 2,7 LM - pack. 20 Pcs - 54 LM

Article	Width mm
PINBFT 45	45
PINBFT 40	40



INSERT +BASE 45/40

